

TB210R

Product Comparison

	Takeuchi TB210R	Bobcat E10	CAT 300.9D	KUBOTA KX008-3	YANMAR SV08-1B
PERFORMANCE					
Tail Swing Design	Short Tail	Zero Tail	Conventional	Conventional	Zero Tail
Operating Weight	2,535 lb (1,150 kg)	2,593 lb (1,176 kg)	2,170 lb (935 kg)	2,200 lb (1,000 kg)	2,348 lb (1,065 kg)
Max Digging Depth	5' 9.1" (1,755 mm)	6' 0" (1,828 mm)	5' 8" (1,731 mm)	5' 8" (1,715 mm)	4' 11" (1,500 mm)
Max Dump Height	6' 11.5" (2,120 mm)	6' 0" (1,828 mm)	6' 8" (2,035 mm)	6' 8" (2,035 mm)	6' 9" (2,050 mm)
Max Reach	10' 9.4" (3,285 mm)	10' 2" (3,098 mm)	10' 1" (3,074 mm)	10' 1" (3,075 mm)	8' 11" (2,730 mm)
Max Bucket Digging Force	3,799 lb (1,723 kg)	1,865 lb (845 kg)	2,000 lb (907 kg)	2,200 lb (1,000 kg)	2,360 lb (1,070 kg)
Max Arm Digging Force	1,440 lb (653 kg)	1,248 lb (566 kg)	1,011 lb (459 kg)	1,010 lb (460 kg)	1,390 lb (630 kg)
Traction Force	2,880 lb (1,306 kg)	NP	NP	1,695 lb (770 kg)	NP
ENGINE					
Make / Model	Kubota D722-E4B	NP	Yanmar 31NV70	Kubota D722-E4	Yanmar 402F-05 EG84548R
Tier Rating	EPA Tier 4 Final	EPA Tier 4 Final	EPA Tier 4 Final	EPA Tier 4 Final	EPA Tier 4 Final
Horsepower	11.7 hp (8.7 kW)	10.2 hp (7.6 kW)	13 hp (9.6 kW)	10.3 hp (7.7 kW)	10.3 hp (7.7 kW)
Rated Engine Speed	2,200 rpm	2,370 rpm	2,100 rpm	2050 rpm	2,800 rpm
Maximum Torque	26.6 ft-lb (36.1 Nm)	NP	NP	NP	NP
UNDERCARRIAGE					
Track Width	7.1" (180 mm)	NP	7" (180 mm)	7.1" (180 mm)	7" (180 mm)
Ground Pressure	4.1 psi (28.0 kPa)	NP	3.5 psi (24.1 kPa)	3.55 psi (24.4 kPa)	NP
Travel Speed Low Range	1.2 mph (2 km/h)	1.3 mph (2.1km/h)	1.12 mph (1.8 km/h)	1.2 mph (2.0 km/h)	1.12 mph (1.8 km/h)
Travel Speed High Range	2.3 mph (3.7 km/h)	1.7 mph (2.7 km/h)	NA	2.5 mph (4.0 km/h)	NP
HYDRAULIC SYSTEM					
Total Hydraulic Flow	7.4 gpm (28 L/m)	NP	6.0 gpm (22.8 L/m)	5.5 gpm (21.0 L/m)	5.2 gpm (19.6 L/m)
Auxiliary Hydraulic Flow	5.9 gpm (22.2 L/m)	5.3 gpm (20.1 L/m)	6.0 gpm (22.8 L/m)	5.5 gpm (21.0 L/m)	5.2 gpm (19.6 L/m)
Hydraulic System Pressure	2,640 psi (18.2 MPa)	2,756 psi (19.0 MPa)	2,466 psi (17 MPa)	NP	2,625 psi (18.1 MPa)
Hydraulic Reservoir Capacity	2.3 gal (9.0 L)	NP	3.7 gal (14.0 L)	3.3 gal (12.5 L)	NP
DIMENSIONS					
Width	29.5 - 40.2 (750-1,020 mm)	28" (711 mm)	28"- 34" (711 mm-864 mm)	28"- 34" (700-864 mm)	27"- 33" (680-840 mm)
Height	7' 2.2" (2,190 mm)	7' 3" (2,210 mm)	7' 6" (2,276 mm)	7' 4" (2,230 mm)	7' 7" (2,300 mm)
Length (Transport)	9' 8.3" (2,955 mm)	9' 2" (2,794 mm)	9' 0" (2,746 mm)	9' 0" (2,750 mm)	8' 6" (2,590 mm)
Ground Clearance	6.3" (160 mm)	NP	5" (127 mm)	5.9" (150 mm)	5.0" (130 mm)
Boom Swing (Degrees L / R)	85 / 85	67 / 64	55 / 56	55 / 60	45 / 90
Min Front Swing Radius	4' 4" (1,320 mm)	NP	3' 9" (1,150 mm)	3' 2" (955 mm)	NP
Tail Swing Radius	2' 0" (610 mm)	NP	2' 5" (736 mm)	2' 6" (750 mm)	2' 5" (725 mm)