

	Takeuchi TB225	Case CX26C	Caterpillar 302 CR	Deere 26G
<b>PERFORMANCE</b>				
Tail Swing Design	Conventional	Short	Short	Short
Operating Weight	4,993 lb (2,265 kg)	5,830 lb (2,645 kg)	4,459 lb (2,023 kg)	5,780 lb (2,620 kg)
Max Digging Depth	8' 6" (2,580 mm)	8' 8" (2,645 mm)	8' 5" (2,600 mm)	8' 6" (2,590 mm)
Max Dump Height	9' 5" (2,875 mm)	9' 11" (3,030 mm)	8' 8" (2,870 mm)	10' 6" (3,190 mm)
Max Reach	14' 4" (4,375 mm)	15' 4" (4,680 mm)	14' 1" (4,267 mm)	15' 2" (4,630 mm)
Max Bucket Digging Force	4,339 lb (1,968 kg)	4,740 lb (2,150 kg)	4,406 lb (1,998 kg)	4,944 lb (2,243 kg)
Max Arm Digging Force	2,877 lb (1,305 kg)	2,880 lb (1,300 kg)	2,203 lb (999 kg)	3,410 lb (1,547 kg)
Traction Force	6,003 lb (2,723 kg)	3,300 lb (1,420 kg)	4,496 lb (2,039 kg)	NP
<b>ENGINE</b>				
Make / Model	Yanmar / 3TNV80F	Kubota / D1305	C1.1	Yanmar / 3TNV80F
Tier Rating	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4
Horsepower	19.6 hp (14.6 kW)	24.8 hp (18.5 kW)	21.0 hp (15.7 kW)	20.0 hp (14.9 kW)
Rated Engine Speed	2,400 rpm	2,300 rpm	2,400 rpm	2,500 rpm
Max Torque	49.7 ft-lb (67.4 Nm)	60 ft-lb (81.4 Nm)	NP	NP
<b>UNDERCARRIAGE</b>				
Track Width	9.8" (250 mm)	9.8" (250 mm)	9.8" (250 mm)	12" (300 mm)
Ground Pressure	4.2 psi (29 kPa)	4.3 psi (29.6 kPa)	NP	3.6 psi (25.0 kPa)
Travel Speed Low Range	1.6 mph (2.5 km/h)	1.5 mph (2.4 km/h)	1.8 mph (2.9 km/h)	1.8 mph (2.9 km/h)
Travel Speed High Range	2.6 mph (4.2 km/h)	2.7 mph (4.3 km/h)	2.7 mph (4.4 km/h)	2.8 mph (4.5 km/h)
<b>HYDRAULIC SYSTEM</b>				
Total Hydraulic Flow	16.6 gpm (62.9 L/m)	14.6 gpm (55.2 L/m)	17.4 gpm (65.8 L/m)	20.1 gpm (76.1 L/m)
Auxiliary Hydraulic Flow	9.96 gpm (37.7 L/m)	12.5 gpm (47.2 L/m)	8.7 gpm (33 L/m)	12.2 gpm (46.2 L/m)
Hydraulic System Pressure	3,045 psi (21.0 Mpa)	3,130 psi (21.6 Mpa)	3,553 psi (24.5 Mpa)	NP
Hydraulic Reservoir Capacity	6.9 gal (26.0 L)	7.1 gal (27 L)	4.8 gal (18.1 L)	6.3 gal (23.8 L)
<b>DIMENSIONS</b>				
Width	43.3"- 59.0" (1,100-1,500 mm)	4' 11" (1,500 mm)	42.9"-55.1" (1,089-1,400 mm)	4' 11" (1,500 mm)
Height	7' 8.8" (2,355 mm)	8' 2" (2,500 mm)	7' 6.6" (2,301 mm)	8' 0" (2,430 mm)
Length (Transport)	14' 4.2" (4,375 mm)	13' 3" (4,030 mm)	12' 8.8" (3,881 mm)	13' 9" (4,180 mm)
Ground Clearance	7.5" (190 mm)	11" (290 mm)	5.9" (149 mm)	12" (305 mm)
Boom Swing (Degrees L / R)	75/55	75 / 50	65/50	70/60
Front Swing Radius	6' 0" (1,830 mm)	NP	5'	6' 4" (1,920 mm)
Tail Swing Radius	4' 0" (1,240 mm)	2' 10" (875 mm)	NP	2' 7" (800 mm)