

	Takeuchi TL10V2	Bobcat T76	Bobcat T740	Caterpillar 289D3	John Deere 325G	Kubota SVL75-2
PERFORMANCE						
Loader Boom Design	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
Operating Weight	9,950 lbs (4,515 kg)	10,250 lbs (4,649 kg)	10,127 lb (4,594 kg)	10,688 lbs (4,847 kg)	9,650 lbs (4,381 kg)	9,039lbs (4,100 kg)
Tipping Load	7,205 lbs (3,268 kg)	8,285 lbs (3,758 kg)	9,143 lb (4,147 kg)	8,255 lbs (3,744kg)	7,400 lbs (3,360 kg)	6,570 lbs (2,980 kg)
Tipping Load w/ CW	7,766 lbs (3,523 kg)	NP	NP	NP	NP	NP
Operating Capacity*	2,522 lbs (1,144 kg)	2,900 lbs (1,315kg)	3,310lb (1,501 kg)	2,890 lbs (1,310 kg)	2,590 lbs (1,176 kg)	2,300 lbs (1,043 kg)
Operating Capacity w/ CW	2,718 lbs (3,954 kg)	NP	NP	NP	NP	NP
Bucket Breakout Force	6,520 lbs (2,957 kg)	NP	NP	7,291 lbs (3,307 kg)	6,000 lbs (2,724 kg)	6,204 lbs (2,814 kg)
Lift Arm Breakout Force	5,400 lbs (2,450 kg)	NP	NP	NP	4,750 lbs (2,154 kg)	4,766 lbs (2,162 kg)
Traction Force	9,730 lbs (4,413 kg)	NP	NP	NP	8,500 lbs (3,850 kg)	9,678 lbs (4.390 kg)

* Operating capacity of track loaders to be rated according to SAE J818 at no more than 35% of the tipping load

ENGINE						
Make / Model	Kubota / V3307CR-TE4B	NP	NP	Cat C3.3B DIT	Yanmar / 4TNV98CT	Kubota / V3307-CR-TE4
Tier Rating	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4
Horsepower	74.3 hp (55.4 kW)	74.0 hp (55.2 kW)	74.0 hp (55.2 kW)	74.3 hp (55.4 kW)	74.0 hp (54.8 kW)	74.3 hp (55.4 kW)
Rated Engine Speed	2,600 rpm	NP	NP	NP	2,500 rpm	2,400 rpm
Maximum Torque	195.5 ft-lb (265 Nm)	NP	NP	195 ft-lb (264 Nm)	207.0 ft-lb (280 Nm)	NP

UNDERCARRIAGE						
Track Width	15.7" (400 mm)	17.7" (450 mm)	17.7" (450 mm)	15.7" (400 mm) 17.7" (450 mm)	15.7" (400 mm)	15.0" (380 mm)
Track Ground Contact Length	4' 7.9" (1,419 mm)	4' 11.2" (1,503 mm)	5' 3.7" (1,618 mm)	5' 4.2" (1,630 mm)	NP	4' 8.5" (1,435 mm)
Ground Pressure	4.9 psi (34.3 kPa)	6.2 psi (42.7 kPa)	4.1 psi (28.3 kPa)	4.7 psi (32.4 kPa)	4.7 psi (32.4 kPa)	4.7 psi (32.4 kPa)
Travel Speed Low Range	4.8 mph (7.7 km / hr)	6.8 mph (10.9 km/h)	6.0 mph (9.6 km/h)	4.5 mph (7.2 km/h)	5.2 mph (8.4 km/h)	4.7 mph (7.6 km/h)
Travel Speed High Range	7.0 mph (11.3 km / hr)	9.2 mph (14.8km/h)	8.3 mph (13.3 km/h)	8.3 mph (13.3 km/h)	8.2 mph (13.2 km/h)	7.1 mph (11.4 km/h)

HYDRAULIC SYSTEM						
Hydraulic Reservoir Capacity	9.5 gal (36.0 L)	NP	NP	10.3 gal (39 L)	NP	9.2 gal (34.8 L)
Auxiliary Flow – Standard	18.8 gpm (71.2 L/m)	23.3 gpm (88.2 L/m)	23.0 gpm (87.1 L/m)	23.0 gpm (87 L/m)	19.0 gpm (70 L/m)	17.4 gpm (65.9 L/m)
Auxiliary Flow – High Flow Option	32.8 gpm (124.0 L/m)	30.3 gpm (114 L/m)	30.5 gpm (115.5 L/m)	32.0 gpm (121 L/m)	27.0 gpm (101 L/m)	29.3 gpm (111 L/m)
Hydraulic System Pressure	3,481 psi (24.0 MPa)	3,500 psi (24.1 mPa)	3,500 psi (24.1 mPa)	3,335 psi (22.9 mPa)	3,450 psi (22.4 mPa)	3,185 psi (22.0 mPa)

DIMENSIONS						
Front Clearance Radius with Bucket	7' 8.5" (2,350 mm)	NP	NP	7' 4.8" (2,256 mm)	6' 8" (2,035 mm)	NP
Rear Clearance Radius	5' 5.2" (1,655 mm)	NP	NP	5' 10.7" (1,796 mm)	NP	NP
Max. Lift Height to Bucket Pin	10' 4.8" (3,170 mm)	10' 8.3" (3,258mm)	10' 11.4" (3,338 mm)	10' 5" (3,178 mm)	10' 6" (3,200 mm)	9' 11" (3,025 mm)
Dump Height Fully Raised	7' 11.9" (2,435 mm)	NP	NP	7' 10" (2,388 mm)	8' 6" (2,593 mm)	7' 4.9" (2,258 mm)
Reach Fully Raised	3' 1.4" (950 mm)	3' 3.9" (1,013 mm)	2' 11.2" (894 mm)	NP	3' 1" (635 mm)	3' 5.7" (1,059 mm)
Overall Width Without Bucket	5' 8.5" (1,740 mm)	6' .9" (1,851 mm)	6' 6" (1,981 mm)	6' 4" (1,930 mm)	6' 3" (1,897 mm)	5' 5.9" (1,674 mm)
Overall Height	7' 5.4" (2,270 mm)	6' 9.8" (2,077 mm)	6' 9.3" (2,065 mm)	6' 11.2" (2,113 mm)	6' 9" (2,057 mm)	6' 10" (2,083 mm)
Minimum Ground Clearance	12.6 in (320 mm)	NP	NP	8.9" (226 mm)	9.3" (236 mm)	11.7" (296 mm)