

	Takeuchi TL6R	ASV RT65	Bobcat T450	Bobcat T62	Caterpillar 239D3	Caterpillar 249D3	Kubota SVL65-2
<b>PERFORMANCE</b>							
Loader Boom Design	Radial	Radial	Radial	Radial	Radial	Radial	Vertical
Operating Weight	7,485 lb (3,395 kg)	7,480 lb (3,143 kg)	6,148 lb (2,789 kg)	8,612 lb (3,906 kg)	7,434 lb (3,372 kg)	7,831 lb (3,552 kg)	8,035 lb (3,645 kg)
Tipping Load	5,269 lb (2,390 kg)	5,550 lb (2,463 kg)	4,000 lb (1,814 kg)	6,143 lb (2,786 kg)	4,370 lb (1,985 kg)	4,970 lb (2,260 kg)	6,000 lb (2,722 kg)
Tipping Load w/ CW	5,831 lb (2,645 kg)	NP	NP	NP	NP	NP	NP
Operating Capacity*	1,841 lb (835 kg)	1,925 lb (861 kg)	1,400 lb (635 kg)	2,150 lb (975 kg)	1,530lb (695 kg)	1,740 lb (790 kg)	2,100 lb (953 kg)
Operating Capacity w/ CW	2,041 lb (925 kg)	NP	NP	NP	NP	NP	NP
Bucket Breakout Force	5,930 lb (2,690 kg)	NP	NP	NP	3,968 lb (1,800 kg)	3,962 lb (1,797 kg)	4,614 lb (2,093 kg)
Lift Arm Breakout Force	4,860 lb (2,205 kg)	NP	NP	NP	NP	NP	4,266 lb (1,935 kg)
Traction Force	8,655 lb (3,926 kg)	NP	NP	NP	NP	NP	8,046 lb (3,813 kg)
* Operating capacity of track loaders to be rated according to SAE J818 at no more than 35% of the tipping load							
<b>ENGINE</b>							
Make / Model	Kubota / V2403-CR-TE4B	Duetz TCD 2.2 T4	Doosan / 2.4L	Doosan / 2.4L	CAT C2.2 CRDI	CAT C2.2 CRDI	V2607-CR-TE4
Tier Rating	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4	EPA Final Tier 4
Horsepower	65.2 hp (48.6 kW)	67.0 hp (44.7 kW)	61.1 hp (45.6 kW)	68.0 hp (50.7 kW)	67.1 hp (50.0 kW)	67.1 hp (50.0 kW)	68.3 hp (51 kW)
Rated Engine Speed	2,700 rpm	NP	2,600 rpm	NP	NP	NP	2,600 rpm
Maximum Torque	146.4 ft-lb (198.5 Nm)	184.4 ft-lb (250 Nm)	NP	NP	153 ft-lb (207 Nm)	153 ft-lb (207 Nm)	NP
<b>UNDERCARRIAGE</b>							
Track Width	12.6" (320 mm)	15" (381 mm)	11.8" (300 mm)	12.6" (320 mm)	12.6" (320 mm) 15.7" (399mm)	12.6" (320 mm) 15.7" (399mm)	12.6" (320 mm) 15" (381mm)
Track Ground Contact Length	4' 6.9" (1,395 mm)	4' 11" (1,499 mm)	4' 2.2" (1,275mm)	4' 6.3" (1,379 mm)	NP	NP	NP
Ground Pressure	4.9 psi (33.7 kPa)	4.2 psi (28.9 kPa)	4.7 psi (32.4 kPa)	5.64 psi (38.8 kPa)	5.6 psi (38.6 kPa)	5.6 psi (38.6 kPa)	4.9 psi (33.8 kPa)
Travel Speed Low Range	4.3 mph (7.0 km/h)	NP	7.3 mph (11.7 km/h)	7.2 mph (11.6 km/h)	7.0 mph (11.3 km/h)	7.0 mph (11.3 km/h)	7.1 mph (11.5 km/h)
Travel Speed High Range	6.2 mph (10.0 km/h)	10.6 mph (17.0 km/h)	11.0 mph (17.7 km/h)	10.2 mph (16.4 km/h)	NA	NA	NA
<b>HYDRAULIC SYSTEM</b>							
Hydraulic Reservoir Capacity	7.9 gal (30.0 L)	3.3 gal (12.4 L)	2.0 gal (7.6 L)	NP	9.0 gal (34.1 L)	9.0 gal (34.1 L)	5.4 gal (20.3 L)
Auxiliary Flow - Standard	17.8 gpm (67.4 L/m)	22.2 gpm (84.0 L/m)	16.7 gpm (63.2 L/m)	17.6 gpm (66.6 L/m)	18.0 gpm (68.1 L/m)	18.0 gpm (68.1 L/m)	17.4 gpm (65.8 L/m)
Auxiliary Flow - High Flow Option	NA	27.4 gpm (103.7 L/m)	NA	26.9 gpm (101.8 L/m)	26 gpm (98.4L/m)	26 gpm (98.4L/m)	27 gpm (102.2L/m)
Hydraulic System Pressure	2,988 psi (20.6 MPa)	3,300 psi (20.6 MPa)	3,300 psi (22.8 MPa)	3,500 psi (24.1 MPa)	3,336 psi (23.0 MPa)	3,336 psi (23.0 MPa)	3,263 psi (22.9 MPa)
<b>DIMENSIONS</b>							
Front Clearance Radius with Bucket	6' 10.5" (2,095 mm)	NP	NP	NP	6' 9.5" (2070 mm)	6' 9.1" (2,060 mm)	NP
Rear Clearance Radius	4' 11.8" (1,520 mm)	NP	NP	NP	4' 9.4" (1,458 mm)	4' 9.4" (1,458 mm)	4' 9.1" (1,451 mm)
Max. Lift Height to Bucket Pin	9' 6.4" (2,905 mm)	9' 8.4" (2,934 mm)	9' 1.5" (2,781 mm)	9' 6.5" (2,908 mm)	9' 3.2" (2,825 mm)	9' 10.2" (3,002 mm)	9' 10.5" (3,010 mm)
Dump Height Fully Raised	7' 5.6" (2,275 mm)	NP	NP	NP	6' 9" (2,057 mm)	7' 4.7" (2,253 mm)	NP
Reach Fully Raised	1' 10" (560 mm)	NP	1' 11.5" (597 mm)	1' 11" (584 mm)	NP	NP	2' 10.9" (886 mm)
Overall Width Without Bucket	5' 0.2" (1,530 mm)	5' 6" (1,676 mm)	4' 7" (1,397 mm)	5' 6.2" (1,681 mm)	5' 6" (1,676 mm)	5' 6" (1,676 mm)	5' 7.9" (1,657 mm)
Overall Height	6' 5.8" (1,975 mm)	6' 9.3" (2,068 mm)	6' 5.8" (1,976 mm)	6' 8.5" (2,044 mm)	6' 8.1" (2,035 mm)	6' 8.3" (2,040 mm)	6' 7.9" (2,029mm)
Minimum Ground Clearance	9.1" (230 mm)	13" (330 mm)	7.3" (185 mm)	NP	7.7" (196 mm)	7.6" (194 mm)	9.1" (233 mm)